



Put the human touch back into parking with two-way video! The 05-211 Video Display delivers a face-to-face interaction between your parking patrons and remote attendants for a 21st century customer experience.

Our 05-211 Video Display provides a significant upgrade over traditional audio-only intercoms by providing your parking patrons a personal interaction. The 10.1" LCD HD screen and USB camera are housed in a durable, steel enclosure and can be used indoors or out with multiple wall, pedestal, and arm mounting options available.



FEATURES

- 10.1" wide viewing angle screen (Sun hood available).
- 5 megapixel HD camera with 120° field of view.
- Thermostat controlled heater for cold weather operation.
- Integrated microphone.
- All-in-one housing for easy installation and versatile mounting options.
- Tough metal case and scratch resistant screen protector that can easily be swapped out.
- Designed & assembled in USA.

SPECIFICATIONS

Camera:	5 megapixel 2592 x 1944 autofocus 120° camera	Operating Temperature:	-35° to 55° Celsius
Screen:	10" 1280 x 800 resolution LED backlit LCD	Relative Humidity Rating:	20% to 90%, non-condensing
Microphone:	High sensitivity omnidirectional	Power Supply Input:	100 - 260 VAC, 47-63 Hz, 1.6A max. 5VDC, 6.0A max
USB Input:	USB 2.0 (Camera)	Mounting:	Integrated 2" x 2" hole pattern
USB Output:	USB 3.0 (Screen)	Physical Dimensions:	10.656" x 1" x 8.394"
Certifications:	FCC Part 15 Pending	Weight:	Less than 5 lbs